EST. 1978

Ammunition Sealing System



AS 5216 Features/Specs:

- Seals Up To 120 ppm
- Seals All Pistol Cartridges
- Seals All Rifle Cartridges Up To & Including 338 Lapua
- Seals Blank Ammunition
- Operator Friendly Color Touchscreen Control/HMI
- Easy Changeover From One Cartridge To Another
- Collator Feeder Supports All Cartridges Up To 338 Lapua
- No Part, No Dispense
- Easy Load R125 Reservoir For 1 Liter Ammo Sealant Bottles
- Precision Sureshot® 3510 Dispensing Valves
- Efficient, No Maintenance Ultracure® 9 UV LED Curing Lamps
- Easy Adjust Micro X,Y,Z Adjustment Slides For Dispense Position
- Vision Inspection Sealant Verification Casemouths & Primers
- Compact Inline Footprint: 24" x 84" x 68"H
- Delivery: 12-16 Weeks ARO

ULTRACURE® 9

UV LED CURING LAMPS

Ultracure® 9 Features/Specifications 365nm High Output LED 24 vdc input power state @ 700 mA 2.8/W cm² maximum output @ 365nm



SURESHOT® 3510

PRECISION DISPENSING VALVES

Sureshot® 3510 Features/Specifications
Compact Weight & Size
Positive Shutoff, No Seals
Cycle Rate Up To 500/Minute
Orifice 0.010 (Included); Other Orifice Sizes Avail.



COLOR TOUCHSCREEN HMI



SURESHOT® 3510 DISPENSING



INSIDE OVERHEAD VIEW

