

SAFETY DATA SHEET

Supertacker 353A

SECTION 1: IDENTIFICATION

- 1.1. Product identifier

Trade name:

Supertacker 353A

Product no.:

MS-353A
- 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive
Restricted to professional and industrial use.

Uses advised against :

None known.
- 1.3. Details of the supplier of the safety data sheet

Company and address:

Hernon Manufacturing Inc

121 Tech Drive

FL 32771 Sanford

USA

T: +1-407-322-4000

www.hernon.com

Contact person:

Hernon SDS Coordinator

E-mail:

customerservice@hernon.com

SDS date:

12/16/2025

SDS Version:

1.0
- 1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webpoisoncontrol (triage.webpoisoncontrol.org) to get specific guidance for your case.

VelocityEHS:

+1-800-255-3924 (USA)

+1-813-248-0585 (International)

1-300-954-583 (Australia)

0-800-591-6042 (Brazil)

400-120-0751 (China)

000-800-100-4086 (India)

800-099-0731 (Mexico)

Contract #: (MIS0002665)

SECTION 2: HAZARD(S) IDENTIFICATION

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Acute Tox. 4; H302, Harmful if swallowed.

Skin Corr. 1; H314, Causes severe skin burns and eye damage.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Dam. 1; H318, Causes serious eye damage.

STOT SE 3; H336, May cause drowsiness or dizziness.

Muta. 1B; H340, May cause genetic defects.

Repr. 2; H361, Suspected of damaging fertility or the unborn child.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

Highly flammable liquid and vapour. (H225)

Harmful if swallowed. (H302)

Causes severe skin burns and eye damage. (H314)

May cause an allergic skin reaction. (H317)

May cause drowsiness or dizziness. (H336)

May cause genetic defects. (H340)

Suspected of damaging fertility or the unborn child. (H361)

May cause damage to organs through prolonged or repeated exposure. (H373)

Precautionary statement(s):

General:

Not applicable.

Prevention:

Obtain special instructions before use. (P201)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Keep container tightly closed. (P233)

Do not breathe vapour/mist. (P260)

Contaminated work clothing should not be allowed out of the workplace. (P272)

Wear eye protection/protective clothing. (P280)

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331)

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. (P303+P361+P353)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. (P305+P351+P338)
 IF exposed or concerned: Get medical advice/attention. (P308+P313)
 Immediately call a POISON CENTER/doctor. (P310)
 Get medical advice/attention if you feel unwell. (P314)
 If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)
 Take off contaminated clothing and wash it before reuse. (P362+P364)
 In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)

Storage: Store in a well-ventilated place. Keep container tightly closed. (P403+P233)
 Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal: Dispose of contents/container in accordance with local regulation. (P501)

Additional labelling: Restricted to professional and industrial use.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
toluene	CAS No.: 108-88-3	30-60%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Repr. 2, H361 STOT RE 2, H373	
Solvent naphtha (petroleum), light aliph.;Low boiling point naphtha;[A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the	CAS No.: 64742-89-8	10-45%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361f	[19]

range of C5 through C10 and boiling in the range of approximately 35°C to 160°C (95°F to 320°F).]				
acetone	CAS No.: 67-64-1	<3%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 , Repeated exposure may cause skin dryness or cracking	
3-trimethoxysilylpropane-1-thiol	CAS No.: 4420-74-0	<1%	Acute Tox. 4, H302 Skin Sens. 1B, H317	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information:

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact:

If skin irritation occurs: Get medical advice/attention.

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion:

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns:

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. A sign warning of toxic materials shall be affixed the room and cupboard containing the product(s).

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Always store in containers of the same material as the original container.

Storage conditions: Keep at temperatures between 7 and 29 °C.
Dry, cool and well ventilated
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Incompatible materials: Bases
Amines
Strong oxidizing agents

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

toluene

Short term exposure limit (STEL) (NIOSH REL) (ppm): 150

Long term exposure limit (ACGIH TLV) (ppm): 20

acetone

Short term exposure limit (STEL) (ACGIH TLV) (ppm): 500

Long term exposure limit (OSHA Table Z-1) (mg/m³): 2400

Long term exposure limit (OSHA Table Z-1) (ppm): 1000

Long term exposure limit (ACGIH TLV) (ppm): 250

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations: Smoking, drinking and consumption of food is not allowed in the work area.

<i>Exposure scenarios:</i>	There are no exposure scenarios implemented for this product.
<i>Exposure limits:</i>	Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.
<i>Appropriate technical measures:</i>	Do not recirculate outlet air that contain the substances. The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Ensure that eyewash stations and safety showers are located within easy reach. Apply standard precautions during use of the product. Avoid inhalation of vapours.
<i>Hygiene measures:</i>	In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.
<i>Measures to avoid environmental exposure:</i>	Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

<i>Generally:</i>	Wash contaminated clothing before reuse. Take off contaminated clothing and wash it before reuse. Use only protective equipment with a recognized certification mark, e.g. the UL mark.
-------------------	---

Respiratory Equipment:

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Skin protection:

Recommended	Type/Category	Standards	
-	Protective Clothing		

Hand protection:

Nitrile Rubber

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Color:</i>	Clear, Colourless
<i>Odor:</i>	Solvent
<i>Odor threshold (ppm):</i>	No data available
<i>pH:</i>	No data available
<i>Density (g/cm³):</i>	0.885
<i>Kinematic viscosity:</i>	No data available
<i>Particle characteristics:</i>	No data available

Phase changes

<i>Melting point/freezing point (°F):</i>	No data available
<i>Softening point/range (°F):</i>	Does not apply to liquids.
<i>Boiling point (°F):</i>	No data available.
<i>Vapor pressure:</i>	No data available.
<i>Relative vapor density:</i>	No data available
<i>Decomposition temperature (°F):</i>	No data available

Data on fire and explosion hazards

<i>Flash point (°F):</i>	No data available
<i>Flash point (°C):</i>	<6 .0
<i>Flammability (°F):</i>	The material is ignitable.
<i>Flammability (°C):</i>	The material is ignitable.
<i>Auto-ignition temperature (°F):</i>	No data available
<i>Explosion limits (% v/v):</i>	No data available

Solubility

<i>Solubility in water:</i>	Very slightly soluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available
<i>Solubility in fat (g/L):</i>	No data available

9.2. Other information

<i>Evaporation rate (n-butylacetate = 100):</i>	No data available
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

Incompatible Materials

Extremes of temperature

Mechanical influences (e.g. Shock, pressure, impact, friction). Fire, sparks or other ignition sources.

10.5. Incompatible materials

Bases

Amines

Strong oxidizing agents

10.6. Hazardous decomposition products

Thermal decomposition may produce corrosive vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

toluene has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Based on available data for the mixture, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data for the mixture, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data for the mixture, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

toluene is listed with EPA Hazardous Waste Number: U220

acetone is listed with EPA Hazardous Waste Number: U002

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
DOT	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L EmS: F-E S-D See below for additional information.
IATA	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.
DOT / See § 172.101 Hazardous Materials Table for any information on special provisions, requirements, or warnings in connection with transport. See § 172.602, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

TSCA (the non-confidential portion): toluene is listed
Solvent naphtha (petroleum), light aliph.;Low boiling point naphtha;[A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C5 through C10 and boiling in the range of approximately 35°C to 160°C (95°F to 320°F).] is listed
acetone is listed
3-trimethoxysilylpropane-1-thiol is listed

Clean Air Act: toluene is regulated as a hazardous air pollutant (HAPS)

EPCRA Section 302: None of the components are listed

EPCRA Section 304: None of the components are listed

EPCRA section 313: toluene is listed

CERCLA: toluene is regulated with a Reportable Quantity (RQ) of: 1000 pounds
acetone is regulated with a Reportable Quantity (RQ) of: 5000 pounds

Hazardous chemical inventory reporting: This product contains substances that may cause endocrine disruption in humans.

State regulations

California / Prop. 65: toluene is known to cause: Developmental Toxicity
NSRL/MADL (µg/day): 7000 (Level represents absorbed dose (rounded from 6,525 µg/day)

Massachusetts / Right To Know Act: toluene is listed
acetone is listed

New Jersey / Right To Know Act: toluene / Substance number: 1866

	toluene is on the Special Health Hazard Substance List
	— acetone / Substance number: 0006 acetone is on the Special Health Hazard Substance List
<i>New York / Right To Know Act:</i>	— toluene is listed toluene is regulated with a Reportable Quantity (RQ) of: 1000 pounds toluene is regulated with a Treshold Reporting Quantity (TRQ) of: 0 pounds
	— acetone is listed acetone is regulated with a Reportable Quantity (RQ) of: 5000 pounds acetone is regulated with a Treshold Reporting Quantity (TRQ) of: 10 pounds
<i>Pennsylvania / Right To Know Act:</i>	— toluene is listed toluene is hazardous to the environment (E)
	— acetone is listed acetone is hazardous to the environment (E)
	—

15.4. Restrictions for application

Restricted to professional and industrial use.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H315, Causes skin irritation.

H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H336, May cause drowsiness or dizziness.
H340, May cause genetic defects.
H350, May cause cancer.
H361, Suspected of damaging fertility or the unborn child.
H361f, Suspected of damaging fertility.
H373, May cause damage to organs through prolonged or repeated exposure.
Repeated exposure may cause skin dryness or cracking, Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CERCLA = Comprehensive Environmental Response Compensation and Liability Act
DOT = Department of Transportation
EINECS = European Inventory of Existing Commercial chemical Substances
EPCRA = Emergency Planning and Community Right-To-Know Act
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HCIS = Hazardous Chemical Information System
HNOC = Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NFPA = National Fire Protection Association
NIOSH = National Institute for Occupational Safety and Health
OECD = Organisation for Economic Co-operation and Development
OSHA = Occupational Safety and Health Administration
PBT = Persistent, Bioaccumulative and Toxic
RCRA = Resource Conservation and Recovery Act
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SARA = Superfund Amendments and Reauthorization Act
SCL = A specific concentration limit.
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

SDS Coordinator

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en