

SAFETY DATA SHEET

External Ammunition Sealant 76301

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name: External Ammunition Sealant 76301
Product no.: MS-76301

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Sealant
Restricted to professional users.
Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **Hernon Manufacturing Inc**
121 Tech Drive
FL 32771 Sanford
USA
T: +1-407-322-4000
www.hernon.com
Contact person: Hernon SDS Coordinator
E-mail: customerservice@hernon.com
SDS date: 5/14/2025
SDS Version: 4.0
Date of previous version: 5/14/2025 (4.0)

1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webpoisoncontrol (triage.webpoisoncontrol.org) to get specific guidance for your case.
VelocityEHS:
+1-800-255-3924 (USA)
+1-813-248-0585 (International)
1-300-954-583 (Australia)
0-800-591-6042 (Brazil)
400-120-0751 (China)
000-800-100-4086 (India)
800-099-0731 (Mexico)
Contract #: (MIS0002665)

SECTION 2: HAZARD(S) IDENTIFICATION

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

2.1. Classification of the substance or mixture

Acute Tox. 4; H302, Harmful if swallowed.
Skin Corr. 1A; H314, Causes severe skin burns and eye damage.
Skin Sens. 1; H317, May cause an allergic skin reaction.
Eye Dam. 1; H318, Causes serious eye damage.
STOT SE 3; H335, May cause respiratory irritation.
Repr. 1B; H360, May damage fertility or the unborn child.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

Harmful if swallowed. (H302)
Causes severe skin burns and eye damage. (H314)
May cause an allergic skin reaction. (H317)
May cause respiratory irritation. (H335)
May damage fertility or the unborn child. (H360)

Precautionary statement(s):

General:

-

Prevention:

Obtain special instructions before use. (P201)
Do not breathe vapour/mist. (P260)
Contaminated work clothing should not be allowed out of the workplace. (P272)
Wear eye protection/protective clothing. (P280)

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331)
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. (P303+P361+P353)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
IF exposed or concerned: Get medical advice/attention. (P308+P313)
Immediately call a POISON CENTER/doctor. (P310)
If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)
Take off contaminated clothing and wash it before reuse. (P362+P364)

Storage:

Store in a well-ventilated place. Keep container tightly closed. (P403+P233)

Disposal:

Dispose of contents/container in accordance with local regulation (P501)

Additional labelling:

Not applicable.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Tetrahydrofurfuryl acrylate	CAS No.: 2399-48-6	30-60%	Corrosive to the respiratory tract Acute Tox. 4, H302 Skin Corr. 1C, H314 Skin Sens. 1B, H317 Eye Dam. 1, H318 Repr. 1B, H360	
Polyethylene Glycol Dimethacrylate	CAS No.: 25852-47-5	7-13%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT SE 3, H335	
2-hydroxyethyl methacrylate	CAS No.: 868-77-9	7-13%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	
Ethoxylated Trimethylolpropane Triacrylate	CAS No.: 28961-43-5	5-10%	Skin Sens. 1B, H317 Eye Irrit. 2, H319	
acrylic acid	CAS No.: 79-10-7	3-7%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Acute Tox. 4, H332 STOT SE 3, H335 (SCL: 1.00 %)	
Hydroxycyclohexyl phenyl ketone	CAS No.: 947-19-3	3-7%		
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	CAS No.: 162881-26-7	3-7%	Skin Sens. 1A, H317	
Cumene hydroperoxide	CAS No.: 80-15-9	<1%	Org. Perox. E, H242 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 (SCL: 10.00 %) Skin Irrit. 2, H315 (SCL: 3.00 %) Eye Dam. 1, H318 Acute Tox. 3, H331 STOT SE 3, H336 STOT RE 2, H373	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information:

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion:

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns:

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Tissue-damaging effects: This product contains substances with skin corrosive properties.

Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼ Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material:

Always store in containers of the same material as the original container.

▼ *Storage conditions:*

Keep at temperatures between 7 and 29 °C.

Dry, cool and well ventilated

Protect from sunlight.

Keep away from any light sources

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Incompatible materials:

Strong oxidizing agents

Reducing agents

Free radical initiators

Inert gas

Peroxides

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No substances are listed with a permissible exposure limit (ref: 29 CFR 1910.1000 TABLE Z-1)

8.2. Exposure controls

Apply general control to prevent unnecessary exposure

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures:

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product.

Avoid inhalation of vapours.

Hygiene measures:

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure:

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment


Generally:

Use only protective equipment with a recognized certification mark, e.g. the UL mark.

Respiratory Equipment:

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.


Skin protection:

Recommended	Type/Category	Standards	
-	Protective Clothing		

Hand protection:

Nitrile Rubber

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Color:

Red

Odor:

Mild

Odor threshold (ppm):

No data available

pH:

No data available

Density (g/cm³):

1.08

Kinematic viscosity:

No data available

Particle characteristics:

Not applicable

Phase changes

Melting point/freezing point (°F):

No data available

Softening point/range (°F):

Does not apply to liquids.

Boiling point (°F):

No data available

Vapor pressure:

No data available

Relative vapor density: No data available

Decomposition temperature (°F): No data available

Data on fire and explosion hazards

Flash point (°F): >201

Flash point (°C): >94

Flammability (°F): No data available

Auto-ignition temperature (°F): No data available

Explosion limits (% v/v): No data available

Solubility

Solubility in water: No data available

n-octanol/water coefficient (LogKow): No data available

Solubility in fat (g/L): No data available

9.2. Other information

Sensitivity to shock: No

Evaporation rate (n-butylacetate = 100): No data available

VOC (g/L): 27.5

Other physical and chemical parameters: No data available.

Oxidizing properties: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies

None known.

10.4. ▼ Conditions to avoid

Extremes of temperature

Sunlight

Incompatible Materials

Other light sources

Mechanical influences (e.g. Shock, pressure, impact, friction). Fire, sparks or other ignition sources.

10.5. Incompatible materials

Strong oxidizing agents

Reducing agents

Inert gas

Free radical initiators

Peroxides

10.6. Hazardous decomposition products

Thermal decomposition may produce corrosive vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Other information

acrylic acid has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.



- 12.4. Mobility in soil
No data available.
- 12.5. Results of PBT and vPvB assessment
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
- 12.6. Other adverse effects
None known.


SECTION 13: DISPOSAL CONSIDERATIONS

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)
acrylic acid is listed with EPA Hazardous Waste Number: U008
Cumene hydroperoxide is listed with EPA Hazardous Waste Number: U096

Specific labelling
Contaminated packing
Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
DOT	UN1760	CORROSIVE LIQUID, N.O.S. (Tetrahydrofurfuryl acrylate)	Transport hazard class: 8 Label: 8 Classification code: C9 	III	No	Limited quantitie s: 5 L Tunnel restrictio n code: (E) See below for additiona l informati on.
IMDG	UN1760	CORROSIVE LIQUID, N.O.S. (Tetrahydrofurfuryl acrylate)	Transport hazard class: 8 Label: 8 Classification code: C9 	III	No	Limited quantitie s: 5 L EmS: F-A S-B See below for additiona l informati

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
						on.
IATA	UN1760	CORROSIVE LIQUID, N.O.S. (Tetrahydrofurfuryl acrylate)	Transport hazard class: 8 Label: 8 Classification code: C9 	III	No	See below for additiona l informati on.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.
DOT / See § 172.101 Hazardous Materials Table for any information on special provisions, requirements, or warnings in connection with transport. See § 172.602, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

<i>TSCA (the non-confidential portion):</i>	Tetrahydrofurfuryl acrylate is listed Polyethylene Glycol Dimethacrylate is listed 2-hydroxyethyl methacrylate is listed Ethoxylated Trimethylolpropane Triacrylate is listed acrylic acid is listed Hydroxycyclohexyl phenyl ketone is listed phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide is listed Cumene hydroperoxide is listed
<i>Clean Air Act:</i>	acrylic acid is regulated as a hazardous air pollutant (HAPS)
<i>EPCRA Section 302:</i>	None of the components are listed
<i>EPCRA Section 304:</i>	None of the components are listed
<i>EPCRA section 313:</i>	acrylic acid is listed Cumene hydroperoxide is listed

<i>CERCLA:</i>	acrylic acid is regulated with a Reportable Quantity (RQ) of: 5000 pounds Cumene hydroperoxide is regulated with a Reportable Quantity (RQ) of: 10 pounds
<i>Hazardous chemical inventory reporting:</i>	This product is subject to Tier II reporting.

State regulations

<i>California / Prop. 65:</i>	None of the components are listed
<i>Massachusetts / Right To Know Act:</i>	acrylic acid is listed Cumene hydroperoxide is listed
<i>New Jersey / Right To Know Act:</i>	acrylic acid / Substance number: 0023 acrylic acid is on the Special Health Hazard Substance List — Cumene hydroperoxide / Substance number: 0543 Cumene hydroperoxide is on the Special Health Hazard Substance List —
<i>New York / Right To Know Act:</i>	acrylic acid is listed acrylic acid is regulated with a Reportable Quantity (RQ) of: 5000 pounds acrylic acid is regulated with a Treshold Reporting Quantity (TRQ) of: 1 pounds — Cumene hydroperoxide is listed Cumene hydroperoxide is regulated with a Reportable Quantity (RQ) of: 10 pounds Cumene hydroperoxide is regulated with a Treshold Reporting Quantity (TRQ) of: 0 pounds —
<i>Pennsylvania / Right To Know Act:</i>	acrylic acid is listed acrylic acid is hazardous to the environment (E) — Cumene hydroperoxide is listed Cumene hydroperoxide is hazardous to the environment (E) —

15.4. Restrictions for application

Restricted to professional users.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

Corrosive to the respiratory tract, Corrosive to the respiratory tract.
H226, Flammable liquid and vapour.
H242, Heating may cause a fire.
H302, Harmful if swallowed.
H312, Harmful in contact with skin.
H314, Causes severe skin burns and eye damage.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H331, Toxic if inhaled.
H332, Harmful if inhaled.
H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.
H360, May damage fertility or the unborn child.
H373, May cause damage to organs through prolonged or repeated exposure.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CERCLA = Comprehensive Environmental Response Compensation and Liability Act
DOT = Department of Transportation
EINECS = European Inventory of Existing Commercial chemical Substances
EPCRA = Emergency Planning and Community Right-To-Know Act
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HCIS = Hazardous Chemical Information System
HNOC = Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NFPA = National Fire Protection Association
NIOSH = National Institute for Occupational Safety and Health
OECD = Organisation for Economic Co-operation and Development
OSHA = Occupational Safety and Health Administration
PBT = Persistent, Bioaccumulative and Toxic
RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

The safety data sheet is validated by

SDS Coordinator

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en